

[54] **HEATING ELEMENT**

[75] **Inventor:** **Jon H. Myer**, Woodland Hills, Calif.

[73] **Assignee:** **Hughes Aircraft Co.**, Los Angeles, Calif.

[21] **Appl. No.:** **627,146**

[22] **Filed:** **Jul. 2, 1984**

[51] **Int. Cl.⁴** **F24H 3/00; H05B 1/00; H01C 3/10**

[52] **U.S. Cl.** **219/354; 219/552; 65/12; 338/280; 338/283**

[58] **Field of Search** **219/354, 353, 357, 549, 219/535, 366, 388 S, 388, 552; 65/12, 18.1, 18.2, 144, 271, 292; 338/283, 284, 279, 280, 281, 214**

[56] **References Cited**

U.S. PATENT DOCUMENTS

2,641,682 6/1953 McKenna 219/10.79
2,688,067 8/1954 Sonnino et al. 219/388 S
3,449,549 6/1969 Isabe et al. 219/388 S

3,525,850 8/1970 Hager, Jr. 219/357

Primary Examiner—C. L. Albritton

Assistant Examiner—M. M. Lateef

Attorney, Agent, or Firm—Lewis B. Sternfels; A. W. Karambelas; Victor G. Laslo

[57] **ABSTRACT**

An electrically energizable high intensity, radiant energy heater (8) having a general M-shape for providing a pocket (20) for localized high intensity isothermal heating for fusion and fiber processing. The heater is shaped to provide easy access for a fiber (18) at an entry (16) to enable insertion of the fiber into the isothermal high temperature zone in pocket (20). A second re-entrant wall external to the pocket provides radiant shielding and buffers the isothermal heating zone from the cool environment. The heater may be constructed from a resistively heated metal, such as platinum foil.

33 Claims, 2 Drawing Figures

